

Pentair Water Membrane Elements

TLC™ (Thin Layer Composite)



Pentair Water Residential Membrane Elements use an industry leading state-of-the-art TLC (Thin Layer Composite) membrane providing high quality water for a broad range of water chemistries. Each membrane is required to meet our factory's strict performance requirements prior to shipment.

Product Features


- TLC Thin Layer Composite membrane
- 100% dry membrane maximizing shelf life
- High rejection stability at high input TDS
- · Standard dimensions to fit in commonly available housings



Pentair Water Membrane Elements

Performance Characteristics


500 ppm



Product Tested at 65 psi; 77°F; 20% recovery; 500 ppm NaCl/RO

Performance Characteristics

2000 ppm



Product Tested at 65 psi; 77°F; 20% recovery; 2000 ppm NaCl/RO




Product Specifications

		Nominal Performance		
Part #	Model	Flow* gpd (lpd)	Rejection*	
555694-00	TLC-50	50 (189)	98%	
555693-00	TLC-75	75 (284)	98%	
655006-00	TLC-24	24 (91)	98%	
655007-00	TLC-36	36 (136)	98%	

 $^{^*}$ Nominal performances are based on a 500 ppm softened tap at 65 psig (4.48 bar), 77°F (25°C), 15% recovery after 24 hours. Individual element flux may vary +/- 15%.

Operational Limits

Max Pressure psi (bar)	100 (6.90)		
Max Temp °F (°C)	120 (49)		
рН	4-11		
Free Chlorine ppm	0.1		



Model	unit	Α	В	С	D	E
TLC-50	inches (cm)	1.79 (4.55)	11.75 (29.85)	10.00 (25.40)	0.875 (2.22)	0.678 (1.72)
TLC-75	inches (cm)	1.79 (4.55)	11.75 (29.85)	10.00 (25.40)	0.875 (2.22)	0.678 (1.72)
TLC-24	inches (cm)	1.79 (4.55)	11.75 (29.85)	10.00 (25.40)	0.875 (2.22)	0.678 (1.72)
TLC-36	inches (cm)	1.79 (4.55)	11.75 (29.85)	10.00 (25.40)	0.875 (2.22)	0.678 (1.72)

Filters and membrane elements are not to be installed on microbiologically unsafe water supplies. TLC Membranes are not certified to sanitize water, remove cysts, bacteria, or viruses. Filter and membrane element performance can be affected by fluctuations in water quality.





5730 North Glen Park Road Milwaukee, WI 53209 Tel: 262.238.4400 Fax: 262.238.4402 Customer Care: 800.279.9404 www.pentairaqua.com/pro